



# ICON 3100-SX+

<b>60</b>	<b>4.2</b>	<b>1</b>
CPU	GHz	TB
CORES	CLOCKSPEED	RAM

The Blackcore ICON range is an overclocked, liquid-cooled server platform for Intel CPUs. Generating ultimate performance for low latency use cases.

Featuring the Intel® Xeon-W 3595X - based on the popular “Sapphire Rapids” architecture - this is a refresh to our extreme core-count “SPR-X” system, which gained popularity for replacing dual-socket systems with a single overclocked NUMA. Now boasting 60 cores.




HTS-84715000 

[Order Now](#) | [Support](#)

# ICON 3122-SX+

2U Vertical




<b>CPU</b>	Intel® Xeon® w7-3595X
<b>CPU Frequency</b>	Up to 60 Cores @ 4.2GHz (all-core) SSE
<b>Cache</b>	112MB @ up to 2.7GHz
<b>Chipset</b>	W790
<b>RAM</b>	Up to 1TB of DDR5 ECC RDIMM Up to 384GB Overclocked ECC RDIMM
<b>PCIe</b>	Slot 1 - Physical x16, Electrical x16, HHFL Double Width Slot 2 - Physical x16, Electrical x16, HHFL Double Width Slot 3 - Physical x16, Electrical x16, HHFL Double Width Slot 4 - Physical x16, Electrical x16, HHFL Single Width
<b>LAN</b>	2 x RJ45 Intel® X710 - 10Gb Ethernet 1 x RJ45 Dedicated IPMI LAN (AST 2600)
<b>Rear I/O</b>	1 x VGA 6 x USB Ports
<b>RAID</b>	Onboard RAID 0, 1, 5, 10 Optional Hardware RAID 0,00,1,10 - no cache Optional Hardware RAID 0,00,1,10,5,6,60 - 4GB cache
<b>Storage</b>	4 x 2.5" SATA <b>OR</b> 2 x 2.5" NVMe hot-swap caddy 4 x M.2 Socket M

<b>OS Compatibility</b>	Minimum - RHEL 7.8+ Recommended - RHEL 9.1+
<b>Management Tools</b>	AMI SCE Redfish
<b>PSU</b>	2000W Dual Redundant (1+1) 230-240V~ 10A MAX. 60-50Hz
<b>Power Connectors</b>	IEC C15/C16
<b>Avg. Power Usage</b>	500W [Idle] 1500W [Load] Power draw based on synthetic load, not including add-in cards.
<b>Operating Temperature</b>	10°C - 27°C (50°F - 80°F)
<b>Dimensions</b>	System: 88 x 438 x 720mm (H x W x D) Boxed: 270 x 990 x 580mm (H x W x D)
<b>Chassis Weight</b>	System: 20KG Boxed: 25KG
<b>Rail Kit</b>	Premium or Short
<b>Certifications</b>	UKCA, CE
<b>Export Code</b>	HTS-84715000

# ICON 3123-SX+

## 2U Horizontal




<b>CPU</b>	Intel® Xeon® w7-3595X
<b>CPU Frequency</b>	Up to 60 Cores @ 4.2GHz [all-core] SSE
<b>Cache</b>	112MB @ up to 2.7GHz
<b>Chipset</b>	W790
<b>RAM</b>	Up to 1TB of DDR5 ECC RDIMM Up to 384GB Overclocked ECC RDIMM
<b>PCIe</b>	Slot 1 - Physical x16, Electrical x16, FHFL Double Width Slot 2 - Physical x16, Electrical x16, HHFL Double Width
<b>LAN</b>	2 x RJ45 Intel® X710 - 10Gb Ethernet 1 x RJ45 Dedicated IPMI LAN (AST 2600)
<b>Rear I/O</b>	1 x VGA 6 x USB Ports
<b>RAID</b>	Onboard RAID 0, 1, 5, 10 Optional Hardware RAID 0,00,1,10 - no cache Optional Hardware RAID 0,00,1,10,5,6,60 - 4GB cache
<b>Storage</b>	4 x 2.5" SATA <b>OR</b> 2 x 2.5" NVMe hot-swap caddy 4 x M.2 Socket M

<b>OS Compatibility</b>	Minimum - RHEL 7.8+ Recommended - RHEL 9.1+
<b>Management Tools</b>	AMI SCE Redfish
<b>PSU</b>	2000W Dual Redundant [1+1] 230-240V~ 10A MAX. 60-50Hz
<b>Power Connectors</b>	IEC C15/C16
<b>Avg. Power Usage</b>	500W [Idle] 1500W [Load] Power draw based on synthetic load, not including add-in cards.
<b>Operating Temperature</b>	10°C - 27°C (50°F - 80°F)
<b>Dimensions</b>	System: 88 x 438 x 720mm [H x W x D] Boxed: 270 x 990 x 580mm [H x W x D]
<b>Chassis Weight</b>	System: 20KG Boxed: 25KG
<b>Rail Kit</b>	Premium or Short
<b>Certifications</b>	UKCA, CE
<b>Export Code</b>	HTS-84715000



# ICON 3132-SX+

3U Vertical



<b>CPU</b>	Intel® Xeon® w7-3595X
<b>CPU Frequency</b>	Up to 60 Cores @ 4.2GHz (all-core) SSE
<b>Cache</b>	112MB @ up to 2.7GHz
<b>Chipset</b>	W790
<b>RAM</b>	Up to 1TB of DDR5 ECC RDIMM Up to 384GB Overclocked ECC RDIMM
<b>PCIe</b>	Slot 1 - Physical x16, Electrical x16, FHFL Single Width Slot 2 - Physical x16, Electrical x16, FHFL Single Width Slot 3 - Physical x16, Electrical x16, FHFL Single Width Slot 4 - Physical x16, Electrical x16, FHFL Single Width Slot 5 - Physical x16, Electrical x16, FHFL Single Width Slot 6 - Physical x16, Electrical x8, FHFL Single Width Slot 7 - Physical x16, Electrical x16, FHFL Single Width
<b>LAN</b>	2 x RJ45 Intel® X710 - 10Gb Ethernet 1 x RJ45 Dedicated IPMI LAN (AST 2600)
<b>Rear I/O</b>	1 x VGA 6 x USB Ports
<b>RAID</b>	Onboard RAID 0, 1, 5, 10 Optional Hardware RAID 0,00,1,10 - no cache Optional Hardware RAID 0,00,1,10,5,6,60 - 4GB cache

<b>Storage</b>	4 x 2.5" SATA <b>OR</b> 2 x 2.5" NVMe hot-swap caddy 4 x M.2 Socket M
<b>OS Compatibility</b>	Minimum - RHEL 7.8+ Recommended - RHEL 9.1+
<b>Management Tools</b>	AMI SCE Redfish
<b>PSU</b>	2000W Dual Redundant (1+1) 230-240V~ 10A MAX. 60-50Hz
<b>Power Connectors</b>	IEC C15/C16
<b>Avg. Power Usage</b>	500W [Idle] 1500W [Load] Power draw based on synthetic load, not including add-in cards.
<b>Operating Temperature</b>	10°C - 27°C (50°F - 80°F)
<b>Dimensions</b>	System: 132 x 438 x 720mm (H x W x D) Boxed: 270 x 990 x 580mm (H x W x D)
<b>Chassis Weight</b>	System: 25KG Boxed: 30KG
<b>Rail Kit</b>	Premium or Short
<b>Certifications</b>	UKCA, CE
<b>Export Code</b>	HTS-84715000

[Order Now](#) | [Support](#)

# Specification Comparison

	ICON 3122-SX+	ICON 3123-SX+	ICON 3132-SX+
<b>Form Factor</b>	2U	2U	3U
<b>Dimensions</b> (H x W x D)	88 x 438 x 720mm	88 x 438 x 720mm	132 x 438 x 720mm
<b>PCIe Compatibility</b>	7* x16 (Physical) HHFL	1* x16 (Physical) FHFL 1* x16 (Physical) HHFL	7* x16 (Physical) FHFL
<b>PCIe Orientation</b>	Vertical	Horizontal	Vertical
<b>PSU</b>	2000W	2000W	2000W
<b>Clock Speed</b>	Up to 60 Cores @ 4.2GHz (SSE)	Up to 60 Cores @ 4.2GHz (SSE)	Up to 60 Cores @ 4.2GHz (SSE)

# Benchmarks

	128GB, 4.18 Kernel	3595X Stock	3595X Blackcore
mlc -r --latency_matrix (ns) [Lower is better]		119.6	92.9
L2->L2 HIT (ns) [Lower is better]		88.6	77.0
PCIe Latency - slot1 (ns) [Lower is better]		507	447
All-core Clock-speed (SSE, GHz) [Higher is better]		2.5	4.2
Peak IPC (prime95, SSE, per thread) [Higher is better]		2.3	4.9